

# Halloween Haunted House Quilt

4x4 5x5 6x6 7x7



Sweet Pea  
MACHINE EMBROIDERY

## Block of the Week Halloween Haunt House Quilt Assembly Instructions

### FABRIC REQUIREMENTS

#### 4x4 (10cm x 10cm) Hoop

##### REST OF THE QUILT (MEASURE YOUR QUILT FIRST)

**Fabric A** - 8cm x 56cm (3" x 22") side borders - optional (**cut later – measure your join blocks first**)

**Fabric B** - 8cm x 48cm (3" x 19") top and bottom borders - optional (**cut later – measure your join blocks first**)

**Fabric C** - 48cm x 69cm (19" x 27") backing (**cut later – measure your join blocks first**)

**Fabric D** - 8cm x 56cm (3" x 98") binding (**cut later – measure your join blocks first**)

**Batting 1** - 8cm x 56cm (3" x 22") side borders - optional (**cut later – measure your join blocks first**)

**Batting 2** – 8cm x 48cm (3" x 19") top and bottom borders - optional (**cut later – measure your join blocks first**)

#### 5x5 (13cm x 13cm) Hoop

##### REST OF THE QUILT (MEASURE YOUR QUILT FIRST)

**Fabric A** - 8cm x 69cm (3" x 27") side borders - optional (**cut later – measure your join blocks first**)

**Fabric B** - 8cm x 56cm (3" x 22") top and bottom borders - optional (**cut later – measure your join blocks first**)

**Fabric C** - 56cm x 81cm (22" x 32") backing (**cut later – measure your join blocks first**)

**Fabric D** - 8cm x 264cm (3" x 104") binding (**cut later – measure your join blocks first**)

**Batting 1** - 8cm x 69cm (3" x 27") side borders - optional (**cut later – measure your join blocks first**)

**Batting 2** - 8cm x 56cm (3" x 22") top and bottom borders - optional (**cut later – measure your join blocks first**)

#### 6x6 (16cm x 16cm) Hoop and 150mm x 150mm Hoop

##### REST OF THE QUILT (MEASURE YOUR QUILT FIRST)

**Fabric A** - 8cm x 81cm (3" x 32") side borders - optional (**cut later – measure your join blocks first**)

**Fabric B** - 8cm x 64cm (3" x 25") top and bottom borders - optional (**cut later – measure your join blocks first**)

**Fabric C** - 64cm x 94cm (25" x 37") backing (**cut later – measure your join blocks first**)

**Fabric D** - 8cm x 330cm (3" x 130") binding (**cut later – measure your join blocks first**)

**Batting 1** - 8cm x 81cm (3" x 32") side borders - optional (**cut later – measure your join blocks first**)

**Batting 2** - 8cm x 64cm (3" x 25") top and bottom borders - optional (**cut later – measure your join blocks first**)

#### 7x7 (18cm x 18cm) Hoop

##### REST OF THE QUILT (MEASURE YOUR QUILT FIRST)

**Fabric A** - 8cm x 94cm (3" x 37") side borders - optional (**cut later – measure your join blocks first**)

**Fabric B** - 8cm x 71cm (3" x 28") top and bottom borders - optional (**cut later – measure your join blocks first**)

**Fabric C** - 71cm x 106cm (28" x 42") backing (**cut later – measure your join blocks first**)

**Fabric D** - 8cm x 371cm (3" x 146") binding (**cut later – measure your join blocks first**)

**Batting 1** - 8cm x 94cm (3" x 37") side borders - optional (**cut later – measure your join blocks first**)

**Batting 2** - 8cm x 71cm (3" x 28") top and bottom borders - optional (**cut later – measure your join blocks first**)

#### Finished Dimensions (approx.) using 15 blocks with 2" finished borders:

**4x4** – 41cmW x 61cmL (16" x 24")

**5x5** – 48cmW x 74cmL (19" x 29")

**6x6** – 56cmW x 86cmL (22" x 34")

**7x7** – 64cmW x 99cmL (25" x 39")

## USING YOUR REGULAR SEWING MACHINE:

### JOINING THE BLOCKS


Lay out your blocks on a flat surface and decide on your layout.



Start off by joining the blocks in rows. Place the first two blocks **right sides** together.



Pin and stitch the side seam on your sewing machine. Stitch just inside the border already stitched on the blocks so the stitching will not be seen on the right side later.





Continue this until you have joined the remaining blocks in that row together.




Continue this until you have each horizontal row of blocks joined.



Open out the stitched seams and press flat.



Next, join the horizontal rows to each other by placing the first two rows right sides together. Pin and stitch the seams on your sewing machine. Stitch just inside the border already stitched on the blocks so the stitching will not be seen on the right side later.



Open out the stitched seams and press flat.



Continue this until you have joined all of the horizontal rows together.



### OPTIONAL: HOW TO ADD BORDERS

Adding borders around your quilt is optional. Skip this section if you don't wish to have borders.

We made our borders 8cm (3") wide. If needed, trim the edges to make them even.

Measure one end of the quilt. Cut two strips of border fabric the length you just measured (**Fabric A**). Then cut two pieces of batting to match (**Batting 1**).



Next, we are going to secure the batting to the border fabric. This can be done in two ways. The first option is to place the border fabric right side up on top of the batting, and with a long basting stitch, sew  $\frac{1}{4}$ " from the edge. Basting the long edges together will prevent them from moving. (Use a bobbin thread that will stand out for this step). The second option is to lightly spray temporary adhesive to the batting and then lay your fabric right side up on the batting.



Place the quilt on top of the border fabric (with the attached batting), right sides together. Pin/clip together.



Stitch together with a half inch seam. (Pinning and stitching on the wrong side of the quilt means you can make sure you are stitching inside the borderline on the front of the quilt. This will ensure this line of stitching will not show on the front).



If you used basting stitches on your borders, go ahead and remove them now. Trim back the batting from the seam allowance.



Fold over and press the side border down neatly.



Repeat for the opposite border.




If needed, trim the borders to make them even.



Now measure one of the side edges without a border (including the new border width in your measurement).




Cut two strips of border fabric the length you just measured (**Fabric B**). Then cut two pieces of batting to match. Repeat the basting stitch method or the use of the temporary adhesive spray that we did for the first two borders (**Batting 2**).





Place the quilt on top of the border fabric (with the attached batting), right sides together. Pin and stitch a ½ inch seam from the edge.



If you used basting stitches on your borders, go ahead and remove them now. Trim back the batting from the seam allowance.



Fold over and press the side border down neatly.



Repeat for the opposite border. If needed, trim the borders to make them even.




## ADDING THE BACKING

Place your backing fabric (**Fabric C**) wrong side up on top of your work surface.

Then place the quilt you have just made right side up on top of the backing fabric (wrong sides together). **Optional** – you can lightly spray your backing down to your quilt to stay in place while attaching the binding. Alternatively, you can baste stitch the backing to the quilt after completing your stitch in the ditch. Place safety pins approximately four inches apart across the whole front of the quilt, going through all layers. This will keep all layers together while you 'stitch in the ditch'.



To join the backing, stitch in the ditch along the border seams and down the middle. We found that stitching in the ditch for the borders and down the middle only was enough for a quilt our size, but ditch stitching on all internal seams can be done, if desired.



Optional: Edge baste all of the edges around the quilt, sandwiching all layers using a 1/4" (6mm) seam with a long stitch. (This just helps keep everything in place when attaching the binding). Once this is done, trim the excess backing fabric so it matches the exact shape of the quilt.




## **PREPARE THE BINDING**

Use your own preferred way of adding the binding to the outer edges of your quilt or follow our method of making a binding.

To make the binding, measure the length and width of the quilt and add them together and then multiply by two. Cut a long strip of fabric this length (if you are cutting one piece of fabric this length, add about an extra 12-16 inches (30-40cm) to the length just to be sure you have enough fabric in the end), or cut a few strips and join them together with your sewing machine as shown. Add extra length if you are joining strips - about 4" (10cm) per strip (**Fabric D**). (The width is optional, but we usually find 3" (8cm) wide sufficient.)



**JOINING STRIPS** - Lay the ends of your fabric strips **right sides** together as shown and sew a diagonal seam from corner to corner (45-degree angle), trim the corner and repeat until all the binding strips are sewn together into one long strip.



Press seam open.



Then fold the whole strip in half, **wrong sides** together and press down.



Lay out your binding fabric and unfold one end. Fold that open end of the binding to a 45-degree angle as shown below and lightly press. Trim your fabric  $\frac{1}{4}$ " from the 45-degree angle fold.



Fold the binding strip in half again as shown below.



Check to see if enough binding has been made. Each corner uses 1" of binding and there needs to be at least 8" (20cm) overlap for finishing.

### **ADDING THE BINDING**

You can work from either the front of the quilt or the back of the quilt. We have decided to stitch our binding to the front of the quilt first to make it easier to hide the border stitching on the front of the quilt.

Match the raw edges of the quilt and the binding to the desired starting location (with your quilt **RIGHT/WRONG SIDE UP**, start about halfway along one side).


Using a ruler, mark one inch down from the end of the strip. Mark with a pin.



Using a ruler, mark three inches down from the one inch mark. Mark with a second pin.



At this time, we also marked a two inch gap above from the first pin. This pin will signal when to stop stitching once we have sewn around the quilt.




Using a 3/8" inch seam, stitch one inch of the open fold onto the quilt and stop stitching when you get to the one inch mark.




Then leave a three inch gap (this will provide an opening to insert the end of the binding fabric when we have completed the sewing). Then start stitching again at the three inch mark.




Continue sewing until you reach the first corner and stop stitching 3/8" (1cm) from the end, but keep your needle down. Lift your foot and turn your quilt (with your needle still down). Continue stitching to the corner.



**DIAGRAM BELOW**



Lift the binding strip over and pull against that angled stitch that we just made to form a diagonal fold. Then fold the binding strip back down creating a fold at the top. Pin and start stitching again until you reach the side of the quilt that you started on, mitring the corners as you go.




Stop stitching when you get to the pin that marks the two inches from the starting point.



Fold up the remaining binding so it sits just above the first three inch mark. Trim the excess binding, leaving enough to slip into the fold. Trim a 1/8" (2-3cm) off the raw edge of the binding for a good one inch (2-3cm). Place the end of the binding fabric into the pocket created at the start of the binding process. Pin in place. Continue to stitch the seam until binding is completely sewn on.







Fold back the binding and press the seams flat.



Now turn the quilt over so you are working on the **BACK/FRONT** of the quilt.



We started at the corner of the quilt. Fold in one side of the corner **JUST** past the stitching and press well. Pin in place. This will help get a nice, pointed corner. Repeat for the other side of the corner, meeting up with the first fold creating a nice, pointed corner. Repeat for all four corners of the quilt.





Then continue folding and pinning the remaining binding to the **BACK/FRONT** of the quilt, **JUST** past the stitching. Once folded, press well.



Start stitching anywhere on the quilt from the front/back using the stitch in the ditch method.



When you get to the corner, simply just leave your needle down and lift the foot and rotate the quilt. Put your foot down and continue stitching in this fashion until you are right around the quilt.



Press.



Enjoy your Haunted House!

